



# OFF-THE-ROAD TYRES





# OFF-THE-ROAD RADIAL TYRES

---





## JS04

- Special pattern design with excellent traction and buoyancy.
- Outstanding stability and operational comfort with large pattern plate and long service life.



Tyre Size	Star Rating	TRA Code	RIM Size (Inches)	Overall Diameter (mm)	Section Width (mm)	Pressure (psi) Max/Min	Load (kg) Max/Min	Speed (km/h) Max/Min	Tread Depth (mm)	Type
17.5R25	★ ★	L3	14.00/1.5	1348	445	94/76	8,500/5,450	50/10	26.5	TL
20.5R25	★ ★	L3	17.00/2.0	1492	520	94/76	11,500/7,300	50/10	28.5	TL
23.5R25	★ ★	L3	19.50/2.5	1617	597	94/76	14,500/9,250	50/10	32.0	TL
26.5R25	★ ★	L3	22.00/3.0	1750	673	94/76	18,500/11,500	50/10	35.0	TL
29.5R25	★ ★	E4/L4	25.00/3.5	1873	750	94/76	22400/14000	50/10	57.0	TL



## JS03

- Versatile tread pattern designed for loader, dozer and other equipment used for construction, stockpile, loading application.
- Super traction and ensures a very comfortable ride.
- The inner liner with special compound helps prevent air leakage.



Tyre Size	Star Rating	TRA Code	RIM Size (Inches)	Overall Diameter (mm)	Section Width (mm)	Pressure (psi) Max/Min	Load (kg) Max/Min	Speed (km/h) Max/Min	Tread Depth (mm)	Type
29.5R25	★ ★	E3/L3	25.00/3.5	1873	750	83/65	14000/22400	50/10	43.0	TL



# INDUSTRIAL BIAS TYRES

---

obs



# SKG+



- Better traction and stability.
- Wide side wall with rim guard protector reduces stress cracking.
- Special compound for tread with chunking, chipping and tear resistance.

Tyre Size	Ply Rating	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure (psi)	Load Capacity (kg)	Max Speed (kmph)	Type	Tread Depth (mm)
10-16.5	10	795	268	75	1,565	25	TL	15
12-16.5	12	825	312	75	2,060	25	TL	16

## L2/G2



- Better traction and stability.
- High performance in normal working condition and chunking, chipping and tear resistance.



Tyre Size	Ply Rating	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure (psi)	Load Capacity (kg)	Max Speed (kmph)	Type	Tread Depth (mm)
10-16.5	10	770	264	59	1,880	25	TL	21

# BHT



- Excellent tread wear resistance with laterally designed lug, also ensures even wear.
- Wide lug design resists buckling, tearing and cracking.



Tyre Size	Ply Rating	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure (psi)	Load Capacity (kg)	Max Speed (kmph)	Type	Tread Depth (mm)
12.5/80-18	12	988	307	53	2650	40	TL	23
12.5/80-18	16	988	307	70	3150	40	TL	24



## R4



- Excellent traction and floatation characteristics.
- Directional tread gives high handling response.



Tyre Size	Ply Rating	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure (psi)	Load Capacity (kg)	Max Speed (kmph)	Type	Tread Depth (mm)
12.5/80-18	12	940	317	53	2625	40	TL	25.5

# BHR SUPER



- Excellent traction.
- Unidirectional tread is capable of resisting chunking, buckling and tearing.

Tyre Size	Ply Rating	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure (psi)	Load Capacity (kg)	Max Speed (kmph)	Type	Tread Depth (mm)
16.9-24	12	1308	440	38	3,250	40	TL	28
16.9-28	12	1410	440	38	3,550	40	TL	30
16.9-28	16	1410	440	38	4,200	40	TL	30
18.4-26	12	1425	475	36	4,000	40	TL	28
18.4-26	16	1425	475	41	4,375	40	TL	28



# BHJ01



- Excellent operation stability.
- Optimum wear resistance.
- Superior self cleaning property.



Tyre Size	Ply Rating	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure (psi)	Load Capacity (kg)	Max Speed (kmph)	Type	Tread Depth (mm)
16.9-28	12	1435	430	29	2,380	40	TL	25
18.4-26	12	1405	448	33	2,985	40	TL	27



# RKB01



- Non-directional tread is capable to withstand cuts, snags and bruises.
- Heavy duty nylon carcass and silica based tread is capable for rough terrain conditions.



Tyre Size	Ply Rating	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure (psi)	Load Capacity (kg)	Max Speed (kmph)	Type	Tread Depth (mm)
15.5-25	16	1278	394	44	7,300	10	TL	25

# SITEKING HD



- Deep tread and excellent tread wear.
- Designed to deliver power to the ground.
- Design offers maximum self cleaning and side slip resistance.



Tyre Size	Ply Rating	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure (psi)	Load Capacity (kg)	Max Speed (kmph)	Type	Tread Depth (mm)
15.5/80-24	16	1260	394	58	3,450	30	TL	32

# R1



- Design offers maximum self cleaning and side slip resistance.
- Designed for better traction.
- Puncture penetration resistance.



Tyre Size	Ply Rating	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure (psi)	Load Capacity (kg)	Max Speed (kmph)	Type	Tread Depth (mm)
15.5/80-24	16	1240	375	50	3,150	30	TL	35



# CMD09



- Tread specially designed to give minimum ground disturbance.
- Suitable for use on soft soil, road construction and similar applications.



Tyre Size	Ply Rating	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure (psi)	Load Capacity (kg)	Max Speed (kmph)	Type	Tread Depth (mm)
23.1-26	16	1560	587	33	4,375	30	TL	26

# EMV01



- Non-directional tread is capable to provide traction and good resistance to slippage.
- Good resistance to abrasion cuts.
- More suitable for construction and municipal works.

Tyre Size	Ply Rating	TRA Code	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure (psi)	Load Capacity (kg)	Max Speed (kmph)	Type	Tread Depth (mm)
17.5-25	20	E3/L3	1350	445	58	4250	50	TL	27
20.5-25	20	E3/L3	1490	520	47	6000	50	TL	29
23.5-25	20	E3/L3	1615	595	43	7300	50	TL	32
26.5-25	28	E3/L3	1743	645	43	9250	50	TL	35

# EMH01



- Special compound makes to perform better on dirt and rock working conditions along with construction and municipal works.
- Non-directional tread is capable to provide traction and good resistance to slippage.
- Good resistance to abrasion cuts.

Tyre Size	Ply Rating	TRA Code	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure (psi)	Load Capacity (kg)	Max Speed (kmph)	Type	Tread Depth (mm)
17.5-25	20	E3/L3	1350	445	58	4250	50	TL	27
20.5-25	20	E3/L3	1490	520	47	6000	50	TL	29
23.5-25	20	E3/L3	1615	595	43	7300	50	TL	32
26.5-25	28	E3/L3	1743	645	43	9250	50	TL	35



# THANK YOU!



USE MASK



DISINFECTION



WASH HAND



DISTANCE

# STAY SAFE!